

Tyres Label Art Foil Paper/H600/ 80g White Glassine Liner

Facestock : Aluminium Art Paper For Tyres

		UNITS	VALUE	TOLERANCE
Weight	ISO536	gsm ²	80	±5
Caliper	ISO534	um	72	±5
Brightness		%	82	
Roughness		uM	-	
Opacity		%	>98	

Adhesive : Rubber Base Glue H600

Aggressive adhesive with a heavy coat weight. Specifically designed for applications on rubber based substrates. Due to the coat weight of this adhesive, precautions must be taken during converting.

		UNITS	VALUE	TOLERANCE
Weight		gsm ²	45	±2
Tack (min)		4.53g	13#	
Shear		-	-	
180° Strength		N	11	
Label Temp Min		°C	5	
Service Temp		°C	-30— +55	

Liner : 80g White Glassine Paper

Super calendared white kraft paper. Primarily used for roll-to-roll label conversion .

		UNITS	VALUE	TOLERANCE
Weight	ISO536	gsm ²	80	±3
Caliper	ISO534	um	65	±5
Transparency	DIN53147	%	48	

Master Width mm 1070

Application

Tyre labels and applications with difficult to adhere to substrates

Storage

One year when stored at 20°C at 50% RH. Avoid direct sunlight and keep storage environment dry and ventilated.

All pressure sensitive materials are sold with the understanding that the purchaser has tested and assessed the material is suitable for the task



BJBallRoll Solutions

AKL +64 9 579 0059

WLT +64 4 472 9079

CHC +64 3 366 0299

DUN +64 3 474 0457